

Installing the D48 Option Into the Model 1100

Following these procedures to install the D48 option in the Model 1100.

1. Remove power connections to the Model 1100.

WARNING:

DISCONNECT POWER FROM THE MODEL 1100 BEFORE ATTEMPTING TO INSTALL THE D48 OPTION. FAILURE TO DO SO MAY RESULT IN DAMAGE TO THE MODEL 1100, PERSONAL INJURY OR DEATH.

2. Lay the unit face down on a table on a soft, clean surface. Make sure the Model 1100 is oriented so that the printing on the rear is upright.
3. Remove the four screws holding the rear cover to the front of the Model 1100. These screws are located on the TOP and SIDES of the unit. Save these screws.
4. Remove the rear cover by carefully lifting it off of the unit.
5. Remove the top blank option cover by removing four screws securing it. Discard the option cover AND the screws holding it in.
6. Replace the top blank option cover with the D48 option card. Secure it with the four screws provided with the option (1/4" 6-32). Make sure the option card is oriented so that it's printing and the printing on the back of the Model 1100 are upright. If a second D48 or an AO3 option is also installed, remove the jumper on W1 from the D48 you are installing and mount the option in the bottom option location. By removing the jumper, the D48 will be referred to as banks 3 & 4. With the jumper, the D48 will be configured as banks 1 & 2 (see the CALL IOBANK command in the Basic Users Guide for more information).

NOTE:

FAILURE TO USE THE SUPPLIED SCREWS WITH THE D48 INSTALLATION KIT MAY RESULT IN DAMAGE OR FAILURE OF THE MODEL 1100 (AND) OR THE D48 OPTION.

7. Connect the option cable to the connector header on the Model 1100 CPU board, making sure to observe the polarizing tab on the cable and its placement onto the connector header.

**NOTE:
FAILURE TO INSERT THE OPTION CABLE INTO THE CPU BOARD CORRECTLY
MAY RESULT IN DAMAGE OR FAILURE OF THE MODEL 1100 (AND) OR THE
D48 OPTION.**

8. Reattach the Model 1100 rear cover to the front casting, making sure no internal cables are pinched or otherwise damaged. Use the same screws to secure the cover that secured it originally.